

# TERRA 25



# TERRA 25 SR


**Part Number:** 1125220 12V DC  
**Application:** ATV / UTV

### Specifications

- Rated Line Pull: 2,500 lbs (1,134 kgs)
- Motor: Sealed 1.3 hp, (.96 kW) Permanent Magnet
- Gearing: 3-Stage Planetary
- Gear Ratio: 140:1
- Sealed Solenoid with Circuit Breaker
- Freespooling Clutch - Ergonomic Control
- Brake: Automatic /100% Load Holding
- Wire Rope 3/16" x 50' (4.8mm x 15.2m)
- Hook: Heavy Duty/Clevis Pinned/Latched
- Heavy Duty 4-way Roller Fairlead
- Remote Control: 10' Sealed Hand-Held & Handle Bar Switch
- Dimensions: 13.2" L x 4.5" D x 4.8" H  
 (335mm L x 114mm D x 122mm H)
- Drum Diameter: Steel 2.0" (50.8mm)
- Drum Length: 3.2" (81.3mm)
- Mounting Bolt Pattern: 3" x 4.87" (76mm x 124mm)
- Installed Weight: 18 lbs. (8.16 kgs.)
- Shipping Weight: 29.51 lbs (13.3 kgs)
- Limited Lifetime Warranty
- UPC 0 22705 00342 1

### Performance (First layer on drum)

Line Pull lb (kg)	Motor Amps	Line Speed FPM (MPM)
0	25	25.0 (7.6)
2,500 (1,134)	162	10.5 (3.2)



**Part Number:** 1125230 12V DC  
**Application:** ATV / UTV

### Specifications

- Rated Line Pull: 2,500 lbs (1,134 kgs)
- Motor: Sealed 1.3 hp, (.96 kW) Permanent Magnet
- Gearing: 3-Stage Planetary
- Gear Ratio: 140:1
- Sealed Solenoid with Circuit Breaker
- Freespooling Clutch - Ergonomic Control
- Brake: Automatic /100% Load Holding
- Synthetic Rope 3/16" x 50' (4.8mm x 15.2m)
- Hook: Heavy Duty/Clevis Pinned/Latched
- Blue Anodized Aluminium Hawse
- Remote Control: 10' Sealed Hand-Held & Handle Bar Switch
- Dimensions: 13.2" L x 4.5" D x 4.8" H  
 (335mm L x 114mm D x 122mm H)
- Drum Diameter: 2.0" (50.8mm)
- Drum Length: 3.2" (81.3mm)
- Mounting Bolt Pattern: 3" x 4.87" (76mm x 124mm)
- Installed Weight: 15 lbs (6.8 kgs.)
- Shipping Weight: 23.70 lbs (10.7 kgs)
- Limited Lifetime Warranty
- UPC 0 22705 00343 8

### Performance (First layer on drum)

Line Pull lb (kg)	Motor Amps	Line Speed FPM (MPM)
0	25	25.0 (7.6)
2,500 (1,134)	162	10.5 (3.2)

